



SteelROCK PACIFIC TILE®

Your permanent solution!

Created using the strength of today's high yield, Galvalume® steel the PACIFIC TILE® provides just the right look for any home without the excessive tile weight. At only 1.5 lbs. / Sq. ft. its one of the lightest roofing tiles on the market today. And by combining the Strength of Steel with the Durability of Rock, offers the best protection for your home.

Whether you need a new roof or a replacement roof, SteelROCK PACIFIC TILE's® angular design and graceful edge slopes within each panel create a rich deep profile to suit any architecture.

The PACIFIC TILE® design helps protect your home from Fire, High-Winds, Hail & Snow, by marrying Steel & Rock into a single shield against time - the permanent solution for your home.



SteelROCK®
ROOF PRODUCTS



PACIFIC TILE®

Strong | Durable | Timeless



Every SteelROCK panel is formed from 26-gauge Galvalume® steel and covered with natural stone granules that are embedded in a 100% acrylic resin basecoat. The panels are then finished with a clear acrylic over-glaze to seal and protect the stone granules.

SteelROCK panels are not only strong, lightweight and durable but they've also surpassed the industry's highest performance tests to date. All of SteelROCK's *blended colors are enhanced with flashes of rock granules in either a dark or light accent to add a subtle beauty to the roof's overall appearance.

The panels are backed by a lifetime* limited warranty covering 120-mph winds and a Class-4 Hail impact (UL 2218) resistance rating. SteelROCK is proud to offer today's homeowners and builders a product that will provide years of maintenance free protection and beauty.

Standard Colors:



Weathered Timber



Birch




Mission Red



Terra Cotta

see website for more color options

Panel Coating Layers



Lifetime Limited Warranty

Non-prorated & fully transferable, *residential single family dwellings, not applicable to entities capable of an infinite life.

Walkable

26-gauge Galvalume® Steel.

Lightweight

1.5 lbs / per sq. ft.

Class-A Fire Rated

Verify correct underlay to meet codes.

120-mph Wind Warranty

Tested in the harshest conditions, can be engineered to meet FL HVHZ wind codes 150-mph.

Hail Impact Warranty

No perforation of the SteelROCK panel from hail
UL 2218 Class-4 rated.

SteelROCK
ROOF PRODUCTS

SteelROCK Roof Products Inc.
721 Monroe Way
Placentia, CA 92870

Phone: 1-800-987-3199
Fax: 1-951-245-1156
www.steelrockroof.com

TESTING CREDENTIALS

ICC Evaluation Report #5218
Miami Dade NOA # 08-0618.02

* Solid colors Charcoal, Mission Red, Pearl White etc. do not receive a flash accent.
Galvalume® is a registered trademark of BIEC International
SteelROCK ©2008, SteelROCK Roof Products, Printed in the U.S.A.
Manufactured by MRP, Oceanside Ca.